



# LIGHT TRUCK TYRES



LIGHT TRUCK TYRES

# LIGHT TRUCK TYRES



## SUPERLUG



| Features   | Benefits   |
|--|--|
| <ul style="list-style-type: none"> <li>• Unique tread compound</li> <li>• Special design with scoops at shoulder</li> <li>• Extra strong casing</li> <li>• Aggressive tread pattern</li> </ul> | <ul style="list-style-type: none"> <li>• Cooler running</li> <li>• Excellent mileage</li> <li>• Better road grip</li> <li>• Better safety and more retreads</li> </ul> |

| TYRE SIZE | PLY RATING | REC-RIM WIDTH (Code) | SECTION WIDTH (mm) | OVERALL DIAMETER (mm) | NON-SKID DEPTH (mm) | LOAD/INFLATION       |                    | STATIC LOADED Radius (mm) | FLAP CODE | TUBE VALVE CODE |
|-----------|------------|----------------------|--------------------|-----------------------|---------------------|----------------------|--------------------|---------------------------|-----------|-----------------|
|           |            |                      |                    |                       |                     | SINGLE kgs@kgs/sq.cm | DUAL kgs@kgs/sq.cm |                           |           |                 |
| 7.00-15   | 12         | 5.5F                 | 205                | 775                   | 16.0                | 1175@6.30            | -                  | 365                       | -         | TR 15           |
| 7.00-16   | 14         | 5.5F                 | 204                | 805                   | 17.0                | 1315@6.90            | 1160@6.90          | 381                       | 16M/16N   | AB 1582         |
| 7.50-16   | 16         | 6.0G                 | 212                | 825                   | 18.0                | 1580@7.75            | 1390@7.75          | 388                       | 16N       | AB 1582         |
| 8.25-16   | 16         | 6.5                  | 229                | 863                   | 19.0                | 1845@ 6.70           | 1755@ 6.70         | 406                       | 16N       | TR 177A         |

## SUPER TRACTION



| Features  | Benefits  |
|---|---|
| <ul style="list-style-type: none"> <li>• Aggressive tread pattern</li> <li>• Strong casing</li> </ul> | <ul style="list-style-type: none"> <li>• Superior traction</li> <li>• High road contact area enhancing road grip</li> <li>• Designed for all wheel fitment</li> </ul> |

| TYRE SIZE | PLY RATING | REC-RIM WIDTH (Code) | SECTION WIDTH (mm) | OVERALL DIAMETER (mm) | NON-SKID DEPTH (mm) | LOAD/INFLATION       |                    | STATIC LOADED Radius (mm) | FLAP CODE | TUBE VALVE CODE |
|-----------|------------|----------------------|--------------------|-----------------------|---------------------|----------------------|--------------------|---------------------------|-----------|-----------------|
|           |            |                      |                    |                       |                     | SINGLE kgs@kgs/sq.cm | DUAL kgs@kgs/sq.cm |                           |           |                 |
| 7.00-15   | 8          | 5.5F                 | 196                | 760                   | 15.3                | 925@4.20             | 816@4.20           | 369                       | -         | TR 75A          |
| 7.00-16   | 8          | 5.5F                 | 198                | 785                   | 15.3                | 966@4.20             | 840@4.20           | 372                       | 16N       | AB 1582         |
| 7.00-16   | 10         | 5.5F                 | 198                | 785                   | 15.3                | 1090@5.25            | 975@5.25           | 372                       | 16N       | AB 1582         |
| 7.50-16   | 8          | 6.0G                 | 210                | 810                   | 15.0                | 1105@4.25            | 970@4.25           | 382                       | 16N       | AB 1582         |
| 7.50-16   | 12         | 6.0G                 | 210                | 810                   | 15.0                | 1405@6.30            | 1240@6.30          | 382                       | 16N       | AB 1582         |

# LIGHT TRUCK TYRES



## M - 77



| Features   | Benefits  |
|--|---|
| <ul style="list-style-type: none"> <li>• Rib lug tread pattern</li> <li>• Aggressive tread design</li> </ul> | <ul style="list-style-type: none"> <li>• All wheel fitment</li> <li>• Better mileage</li> <li>• Excellent traction</li> </ul> |

| TYRE SIZE | PLY RATING | REC-RIM WIDTH (Code) | SECTION WIDTH (mm) | OVERALL DIAMETER (mm) | NON-SKID DEPTH (mm) | LOAD/INFLATION       |                    | STATIC LOADED Radius (mm) | FLAP CODE | TUBE VALVE CODE |
|-----------|------------|----------------------|--------------------|-----------------------|---------------------|----------------------|--------------------|---------------------------|-----------|-----------------|
|           |            |                      |                    |                       |                     | SINGLE kgs@kgs/sq.cm | DUAL kgs@kgs/sq.cm |                           |           |                 |
| 7.00-15   | 10         | 5.5F                 | 205                | 780                   | 15.2                | 1050@5.25            | 925@5.25           | 367                       | -         | TR 15           |
| 7.00-15   | 12         | 5.5F                 | 205                | 780                   | 15.2                | 1175@6.30            | 1030@6.30          | 367                       | -         | TR 15           |
| 7.50-16   | 14         | 6.0G                 | 213                | 827                   | 18.0                | 1495@7.05            | 1315@7.05          | 391                       | 16N       | AB1582          |

## SUPERMILER



| Features  | Benefits   |
|---|--|
| <ul style="list-style-type: none"> <li>• 5 rib design pattern</li> <li>• Unique fan like shoulder design</li> </ul> | <ul style="list-style-type: none"> <li>• Good mileage and traction</li> <li>• Better retreadability</li> </ul> |

| TYRE SIZE   | PLY RATING | REC-RIM WIDTH (Code) | SECTION WIDTH (mm) | OVERALL DIAMETER (mm) | NON-SKID DEPTH (mm) | LOAD/INFLATION       |                    | STATIC LOADED Radius (mm) | FLAP CODE | TUBE VALVE CODE |
|-------------|------------|----------------------|--------------------|-----------------------|---------------------|----------------------|--------------------|---------------------------|-----------|-----------------|
|             |            |                      |                    |                       |                     | SINGLE kgs@kgs/sq.cm | DUAL kgs@kgs/sq.cm |                           |           |                 |
| LT215/80D14 | 10         | 5.5J                 | 211                | 691                   | 11.0                | 1125@5.25            | -                  | 324                       | -         | TR 13           |
| LT215/80D14 | 10         | 5.5J                 | 211                | 691                   | 11.0                | 1125@5.25            | -                  | 324                       | -         | TUBELESS        |
| 6.70-15     | 8          | 5.0K                 | 180                | 718                   | 12.0                | 820@4.25             | -                  | 335                       | -         | TR 15           |
| 7.00-15     | 8          | 5.5F                 | 200                | 772                   | 12.5                | 925@4.25             | -                  | 363                       | -         | TR 15           |
| 7.00-15     | 10         | 5.5F                 | 200                | 772                   | 12.5                | 1050@5.25            | -                  | 363                       | -         | TR 15           |
| 6.50-16     | 8          | 4.5F                 | 174                | 753                   | 12.5                | 860@4.25             | -                  | 355                       | -         | TR 15           |
| 7.00-16     | 10         | 5.5F                 | 204                | 797                   | 12.5                | 1100@5.25            | 965@5.25           | 372                       | 16N       | AB1582          |
| 7.00-16     | 12         | 5.5F                 | 204                | 797                   | 12.5                | 1215@6.20            | 1065@6.20          | 378                       | 16N       | AB1582          |
| 7.50-16     | 12         | 6.0G                 | 207                | 810                   | 13.0                | 1405@6.30            | 1240@6.30          | 382                       | 16N       | AB1582          |
| 7.50-16     | 14         | 6.0G                 | 207                | 810                   | 13.0                | 1495@7.05            | 1315@7.05          | 382                       | 16N       | AB1582          |
| 8.25-16     | 16         | 6.5                  | 229                | 854                   | 14.0                | 1845@ 6.70           | 1755@ 6.70         | 402                       | 16N       | TR 177A         |



## HIGHWAY



| Features   | Benefits   |
|--|--|
| <ul style="list-style-type: none"> <li>• Unique rib tread pattern</li> <li>• Free rolling tread design</li> <li>• Cooler running compound</li> </ul> | <ul style="list-style-type: none"> <li>• Good road grip</li> <li>• Good mileage</li> </ul> |

| TYRE SIZE | PLY RATING | REC-RIM WIDTH (Code) | SECTION WIDTH (mm) | OVERALL DIAMETER (mm) | NON-SKID DEPTH (mm) | LOAD/INFLATION       |                    | STATIC LOADED Radius (mm) | FLAP CODE | TUBE VALVE CODE |
|-----------|------------|----------------------|--------------------|-----------------------|---------------------|----------------------|--------------------|---------------------------|-----------|-----------------|
|           |            |                      |                    |                       |                     | SINGLE kgs@kgs/sq.cm | DUAL kgs@kgs/sq.cm |                           |           |                 |
| 7.00-15   | 8          | 5.5F                 | 200                | 757                   | 11.2                | 925@4.20             | 815@4.20           | 367                       | -         | TR 15           |
| 7.00-16   | 8          | 5.5F                 | 200                | 783                   | 11.2                | 965@4.20             | 850@4.20           | 371                       | 16N       | AB1582          |
| 7.50-16   | 8          | 6.0G                 | 212                | 810                   | 11.5                | 1105@4.25            | 970@4.25           | 382                       | 16N       | AB1582          |
| 7.50-16   | 12         | 6.0G                 | 212                | 810                   | 11.5                | 1405@6.30            | 1240@6.30          | 382                       | 16N       | AB1582          |
| 7.50-16   | 14         | 6.0G                 | 215                | 824                   | 11.5                | 1495@7.00            | 1315@7.00          | 387                       | 16N       | AB1582          |

## LCV RADIAL



## STEEL MUSCLE

| Features  | Benefits  |
|---|---|
| <ul style="list-style-type: none"> <li>• 4 rib design</li> <li>• Unique tread compound</li> </ul> | <ul style="list-style-type: none"> <li>• Enhanced mileage and traction</li> <li>• Better road grip</li> </ul> |

| TYRE SIZE   | PLY RATING | REC-RIM WIDTH (Code) | SECTION WIDTH (mm) | OVERALL DIAMETER (mm) | NON-SKID DEPTH (mm) | LOAD/INFLATION       |                    | STATIC LOADED Radius (mm) | FLAP CODE | TUBE VALVE CODE |
|-------------|------------|----------------------|--------------------|-----------------------|---------------------|----------------------|--------------------|---------------------------|-----------|-----------------|
|             |            |                      |                    |                       |                     | SINGLE kgs@kgs/sq.cm | DUAL kgs@kgs/sq.cm |                           |           |                 |
| LT 7.00 R15 | 10         | 5.5                  | 206                | 755                   | 12.5                | 1050@5.60            | -                  | 350                       | -         | TR 150          |



## STEEL MUSCLE - L



| Features   | Benefits   |
|--|--|
| <ul style="list-style-type: none"> <li>• Specially designed tread block</li> <li>• Good retreadability</li> <li>• Specially designed tread compound</li> </ul> | <ul style="list-style-type: none"> <li>• Low heat generation</li> <li>• Excellent traction &amp; gripping</li> <li>• Long wear life</li> </ul> |

| TYRE SIZE     | PLY RATING | REC-RIM WIDTH (Code) | SECTION WIDTH (mm) | OVERALL DIAMETER (mm) | NON-SKID DEPTH (mm) | LOAD/INFLATION       |                    | STATIC LOADED Radius (mm) | FLAP CODE | TUBE VALVE CODE |
|---------------|------------|----------------------|--------------------|-----------------------|---------------------|----------------------|--------------------|---------------------------|-----------|-----------------|
|               |            |                      |                    |                       |                     | SINGLE kgs@kgs/sq.cm | DUAL kgs@kgs/sq.cm |                           |           |                 |
| LT 185 R 14   | 8          | 5.5J                 | 189                | 654                   | 10.5                | 850@4.6              | 800@4.6            | 302                       | -         | TR 13           |
| LT 7.00 R 16  | 10         | 5.5F                 | 203                | 778                   | 12.5                | 1100@5.6             | 965@5.6            | 362                       | 16N       | TR 15           |
| LT 7.00 R 16  | 12         | 5.5                  | 203                | 778                   | 12.5                | 1215@6.7             | 1065@6.7           | 362                       | 16N       | TR 15           |
| LT 7.50 R 16  | 14         | 6.0                  | 212                | 814                   | 12.5                | 1495@7.40            | 1315@7.40          | 375                       | 16N       | TR 15           |
| LT185/85 R 16 | 8          | 6.0J                 | 185                | 725                   | 9.5                 | 925@4.58             | -                  | 335                       | -         | -               |

## STEEL MUSCLE - R



| Features  | Benefits  |
|---|---|
| <ul style="list-style-type: none"> <li>• Exclusive highway application</li> <li>• Rib design for excellent resistance to uneven wear</li> </ul> | <ul style="list-style-type: none"> <li>• Good maneuverability</li> <li>• Excellent mileage</li> <li>• Good cornering control</li> </ul> |

| TYRE SIZE    | PLY RATING | REC-RIM WIDTH (Code) | SECTION WIDTH (mm) | OVERALL DIAMETER (mm) | NON-SKID DEPTH (mm) | LOAD/INFLATION       |                    | STATIC LOADED Radius (mm) | FLAP CODE | TUBE VALVE CODE |
|--------------|------------|----------------------|--------------------|-----------------------|---------------------|----------------------|--------------------|---------------------------|-----------|-----------------|
|              |            |                      |                    |                       |                     | SINGLE kgs@kgs/sq.cm | DUAL kgs@kgs/sq.cm |                           |           |                 |
| LT 185 R 14  | 8          | 5.5                  | 189                | 654                   | 10.5                | 850@4.6              | 800@4.6            | 302                       | -         | TR 13           |
| LT 7.00 R 16 | 10         | 5.5                  | 203                | 778                   | 12.5                | 1100@5.6             | 965@5.6            | 362                       | 16N       | TR 15           |
| LT 7.00 R 16 | 12         | 5.5                  | 203                | 778                   | 12.5                | 1215@6.7             | 1065@6.7           | 362                       | 16N       | TR 15           |



## STEEL MUSCLE

| Features  | Benefits  |
|---|---|
| <ul style="list-style-type: none"> <li>• 4 rib design</li> <li>• Unique tread compound</li> </ul> | <ul style="list-style-type: none"> <li>• Enhanced mileage and traction</li> <li>• Better road grip</li> </ul> |

| TYRE SIZE   | PLY RATING | REC-RIM WIDTH (Code) | SECTION WIDTH (mm) | OVERALL DIAMETER (mm) | NON-SKID DEPTH (mm) | LOAD/INFLATION       |                    | STATIC LOADED Radius (mm) | FLAP CODE | TUBE VALVE CODE |
|-------------|------------|----------------------|--------------------|-----------------------|---------------------|----------------------|--------------------|---------------------------|-----------|-----------------|
|             |            |                      |                    |                       |                     | SINGLE kgs@kgs/sq.cm | DUAL kgs@kgs/sq.cm |                           |           |                 |
| LT 7.50 R16 | 14         | 6.0                  | 214                | 815                   | 12.5                | 1495@7.40            | 1315@7.40          | 381                       | 16N       | AB1582          |
| LT 7.50 R16 | 12         | 6.0                  | 212                | 814                   | 12.5                | 1405@6.70            | 1240@6.70          | 375                       | 16N       | TR 15           |



## ZQT

| Features   | Benefits   |
|--|--|
| <ul style="list-style-type: none"> <li>• Specially designed tread pattern for even wear</li> <li>• Excellent all-season performance</li> </ul> | <ul style="list-style-type: none"> <li>• Excellent mileage</li> <li>• Enhanced road grip</li> <li>• Smooth and quiet ride</li> </ul> |

| TYRE SIZE  | PLY RATING | REC-RIM WIDTH (Code) | SECTION WIDTH (mm) | OVERALL DIAMETER (mm) | NON-SKID DEPTH (mm) | LOAD/INFLATION       |                    | STATIC LOADED Radius (mm) | FLAP CODE | TUBE VALVE CODE |
|------------|------------|----------------------|--------------------|-----------------------|---------------------|----------------------|--------------------|---------------------------|-----------|-----------------|
|            |            |                      |                    |                       |                     | SINGLE kgs@kgs/sq.cm | DUAL kgs@kgs/sq.cm |                           |           |                 |
| 195/70 R14 | 6          | 6.0J                 | 196                | 632                   | 10.5                | 690@2.96             | -                  | 292                       | -         | -               |
| 235/70 R16 | 6          | 7J                   | 236                | 733                   | 10.3                | 925@2.45             | -                  | 328                       | -         | -               |
| 215 R14    | 112/110P   | 6J                   | 216                | 704                   | 12.25               | 1120@4.6             | 160@4.6            | 324                       | -         | -               |
| 235/75 R15 | 105Q       | 6.5J                 | 235                | 733                   | 10.75               | 925@2.45             | -                  | 328                       | -         | -               |
| 265/70 R16 | 112Q       | 8J                   | 272                | 778                   | 10.75               | 1120@2.45            | -                  | 348                       | -         | -               |

# LIGHT TRUCK TYRES



## ZGT



| Features  | Benefits  |
|---|---|
| <ul style="list-style-type: none"> <li>• Futuristic design</li> <li>• Bold block tread pattern</li> <li>• Sporty looks</li> </ul> | <ul style="list-style-type: none"> <li>• Excellent traction</li> <li>• Quick handling response</li> </ul> |

| TYRE SIZE   | PLY RATING | REC-RIM WIDTH (Code) | SECTION WIDTH (mm) | OVERALL DIAMETER (mm) | NON-SKID DEPTH (mm) | LOAD/INFLATION       |                    | STATIC LOADED Radius (mm) | FLAP CODE | TUBE VALVE CODE |
|-------------|------------|----------------------|--------------------|-----------------------|---------------------|----------------------|--------------------|---------------------------|-----------|-----------------|
|             |            |                      |                    |                       |                     | SINGLE kgs@kgs/sq.cm | DUAL kgs@kgs/sq.cm |                           |           |                 |
| LT 195 R 15 | 8          | 5.5K                 | 197                | 697                   | 10.5                | 950@4.6              | -                  | 321                       | -         | TR 13           |

## ZGP



| Features   | Benefits   |
|--|--|
| <ul style="list-style-type: none"> <li>• Bold block tread pattern</li> <li>• All terrain tread compound</li> </ul> | <ul style="list-style-type: none"> <li>• Excellent even on rugged terrains</li> <li>• Enhanced breaking and stability</li> </ul> |

| TYRE SIZE     | PLY RATING | REC-RIM WIDTH (Code) | SECTION WIDTH (mm) | OVERALL DIAMETER (mm) | NON-SKID DEPTH (mm) | LOAD/INFLATION       |                    | STATIC LOADED Radius (mm) | FLAP CODE | TUBE VALVE CODE |
|---------------|------------|----------------------|--------------------|-----------------------|---------------------|----------------------|--------------------|---------------------------|-----------|-----------------|
|               |            |                      |                    |                       |                     | SINGLE kgs@kgs/sq.cm | DUAL kgs@kgs/sq.cm |                           |           |                 |
| LT 235/75 R15 | 6          | 6.5J                 | 240                | 735                   | 12.5                | 900@3.5              | 825@3.5            | 334                       | -         | TR 13           |





## JOGGER - A/T



| Features   | Benefits  |
|--|---|
| <ul style="list-style-type: none"> <li>• Bold aggressive pattern</li> <li>• Excellent traction</li> <li>• All terrain rugged design</li> </ul> | <ul style="list-style-type: none"> <li>• Excellent ride control</li> <li>• Long life</li> </ul> |

| TYRE SIZE | PLY RATING | REC-RIM WIDTH (Code) | SECTION WIDTH (mm) | OVERALL DIAMETER (mm) | NON-SKID DEPTH (mm) | LOAD/INFLATION       |                    | STATIC LOADED Radius (mm) | FLAP CODE | TUBE VALVE CODE |
|-----------|------------|----------------------|--------------------|-----------------------|---------------------|----------------------|--------------------|---------------------------|-----------|-----------------|
|           |            |                      |                    |                       |                     | SINGLE kgs@kgs/sq.cm | DUAL kgs@kgs/sq.cm |                           |           |                 |
| 6.50 R 16 | 8          | 4.5                  | 185                | 750                   | 10.5                | 920@4.85             | 870@4.85           | 339                       | -         | -               |

## ZVTS



| Features   | Benefits   |
|--|--|
| <ul style="list-style-type: none"> <li>• Carcass incorporates supple sidewalls</li> <li>• Deeper tread grooves in an optimised tread design</li> <li>• Tread design features higher sipe density and computerised tread pitch sequence</li> <li>• Premium all-season tread compound</li> </ul> | <ul style="list-style-type: none"> <li>• Supple sidewalls for comfort &amp; reliability</li> <li>• Outstanding traction and responsive braking capability</li> <li>• Optimum traction and a smooth, quiet ride</li> <li>• Special polymer compound provides long-term even tread wear</li> </ul> |

| TYRE SIZE   | PLY RATING | REC-RIM WIDTH (Code) | SECTION WIDTH (mm) | OVERALL DIAMETER (mm) | NON-SKID DEPTH (mm) | LOAD/INFLATION       |                    | STATIC LOADED Radius (mm) | FLAP CODE | TUBE VALVE CODE |
|-------------|------------|----------------------|--------------------|-----------------------|---------------------|----------------------|--------------------|---------------------------|-----------|-----------------|
|             |            |                      |                    |                       |                     | SINGLE kgs@kgs/sq.cm | DUAL kgs@kgs/sq.cm |                           |           |                 |
| LT 175 R 14 | 6          | 5J                   | 180                | 635                   | 9.5                 | 710@3.86             | 670@3.86           | 280                       | -         | -               |